

Specific energy storage applications alofi

,?,:?,,?,,?...

Thank you for visiting nature . You are using a browser version with limited support for CSS. To obtain the best experience, we recommend you use a more up to date browser (or turn off compatibility mode in Internet Explorer). In the meantime, to ensure continued support, we are displaying the site without styles and JavaScript.

Perovskite oxides have garnered substantial attention in recent years due to their diverse and exceptional properties, making them compelling candidates for various applications, especially in the realm of energy storage technology. This class of materials exhibits a distinctive crystal structure characterized by the general formula ABX_3 , where A is typically an alkaline earth metal, B is a transition metal, and X is an anion⁴.

In the context of perovskite oxides, alkaline earth-based titanates, particularly those derived from barium (Ba) and strontium (Sr), have emerged as pivotal contributors to advancements in energy storage technologies. The unique combination of their crystal structure and electrochemical properties makes them promising candidates for applications such as supercapacitor electrodes^{4,5,6}.

The $MTiO_3$ series, which includes elements like Mg, Mn, Ni, and others, is of particular interest due to its exceptional dielectric constant and remarkably high-quality factor. These unique properties in perovskite titanates stem from the arrangement of TiO_6 octahedra, which are isolated by MO_6 octahedra and cation vacancies. Each layer of MO_6 octahedra is situated between two layers of TiO_6 octahedra, contributing to these distinctive characteristics^{3,7,8}.

The utilization of $MgTiO_3$ extends across various domains, contingent upon the specific modifiers employed. When $MgTiO_3$ is modified with rare earth metals, its applications encompass a wide range of areas, including light-emitting and photovoltaic applications, plasma and flat panel devices, light-emitting and solid-state diodes, and optical devices, among others^{13,14}. Meanwhile, $MgTiO_3$ modified with transition metal ions can be used in microwave, satellite, and terrestrial communication, including radio software, GPS, and DBSTV for environmental monitoring¹⁵.

Perovskite materials at the nanoscale exhibit distinctive features, including extensive porous structures, a significant surface area, regulated transport and charge-carrier mobility, potent absorption, and photoluminescence. Additionally, their unique adaptability in terms of composition, morphology, and functionalities candidate perovskite nanocrystals as highly effective elements for energy applications such as photovoltaics, catalysis, thermoelectrics, batteries, supercapacitors, and hydrogen storage systems^{19,20,21,22}.

The electrochemical performance of supercapacitors depends on electrode materials, electrolytes, and potential

windows. Metal oxides are extensively employed in energy storage and conversion applications, mainly due to their cost-effectiveness, abundant availability, ease of preparation, multiple valence states, and environmental friendliness. They find applications in various fields, including sensors^{23,24,25,26}, biosensors^{27,28}, lithium batteries²⁹, supercapacitors^{30,31,32}, electrocatalysis, and fuel cells.

The current work aims to fabricate MgTiO_3 modified with Li^+ to extend their application in energy storage systems, including lithium-ion batteries and supercapacitors. The production of Li-MgTiO_3 as a dielectric nanoceramic material for supercapacitors was achieved via the acetic acid sol-gel method, followed by 3-h calcination at $800\text{ }^\circ\text{C}$ to promote crystalline development. This research explores into evaluating the electrical and optical attributes of the resultant Li-MgTiO_3 perovskite nano-ceramics, encompassing properties such as impedance, Cole-Cole plot analysis, conductivity, absorbance, and energy band gap.

The electrochemical studies were produced by using impedance and cyclic voltammetry electrochemical techniques. The modified screen-printed electrode exhibited remarkably electrocatalytic properties, proving effective in direct electrochemical applications. Notably, this synthesis approach holds significance for advancing energy storage applications.

This study ensures a comprehensive exploration of the doping mechanisms, contributing valuable insights into the tailored design of titanate-based materials for enhanced energy storage applications.

Initially, the synthesis of MgTiO_3 (MT) was carried out using the sol-gel reaction method. All the necessary chemicals were procured from Sigma Aldrich. The procedure commenced by dissolving precise amounts of highly pure magnesium acetate ($\text{Mg}(\text{CH}_3\text{COO})_2 \cdot 4\text{H}_2\text{O}$) in 15 mL of water and acetic acid with continuous stirring. The required stoichiometric quantities of titanium isopropoxide were dissolved in acetylacetone ($\text{CH}_3\text{COCH}_2\text{COCH}_3$) and introduced into the previously mentioned solution while maintaining a temperature of $50\text{ }^\circ\text{C}$.

Contact us for free full report

Web: <https://kary.com.pl/contact-us/>

Email: energystorage2000@gmail.com

WhatsApp: 8613816583346

